

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : BUFFER SOLUTION PH 5.00 ± 0.01 AT 20°C  
Type of product : Solution

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

ISOLAB Laborgeräte GmbH  
Am Dillhof 2 - 63863 Eschau / GERMANY  
Tel: + 49 93 74 / 978 55-0  
Fax: +49 93 74 / 978 55-29  
[prodsafe@isolab.de](mailto:prodsafe@isolab.de)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Giftnotruf der Charité CBF, Haus VIII (Wirtschaftgebäude), UG	Hindenburgdamm 30 12203 Berlin	+49 30 19240	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
potassium hydrogen phthalate	(CAS-No.) 877-24-7 (EC-No.) 212-889-4	0.1 - 2.5	Not classified
mercury diiodide	(CAS-No.) 7774-29-0 (EC-No.) 231-873-8 (EC Index-No.) 080-002-00-6	< 0.1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 1 (Dermal), H310 Acute Tox. 2 (Oral), H300 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
potassium iodide	(CAS-No.) 7681-11-0 (EC-No.) 231-659-4	< 0.1	Not classified

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



sodium hydroxide, caustic soda	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5 (EC Index-No.) 011-002-00-6 (REACH-no) 01-2119457892-27	< 0.1	Skin Corr. 1A, H314 Eye Dam. 1, H318 Met. Corr. 1, H290
--------------------------------	---	-------	---

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
mercury diiodide	(CAS-No.) 7774-29-0 (EC-No.) 231-873-8 (EC Index-No.) 080-002-00-6	(C >= 0.1) STOT RE 2, H373
sodium hydroxide, caustic soda	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5 (EC Index-No.) 011-002-00-6 (REACH-no) 01-2119457892-27	( 0.5 =<C < 2) Skin Irrit. 2, H315 ( 0.5 =<C < 2) Eye Irrit. 2, H319 ( 2 =<C < 5) Skin Corr. 1B, H314 (C >= 5) Skin Corr. 1A, H314

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>mercury diiodide (7774-29-0)</b>		
EU	IOELV TWA (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup> (Mercury, divalent inorganic compounds; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Mercure et composés inorganiques bivalents du mercure, y compris l'oxyde de mercure et le chlorure mercurique (mesurés comme mercure) (8); Belgium; Time-weighted average exposure limit 8 h)
France	VME (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup> (Mercure et composés bivalents du mercure, y compris l'oxyde de mercure et le chlorure de mercurique; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup> (Kwik en tweewaardige anorganische kwikverbindingen (gemeten als kwik); Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value; als Hg)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	0.02 mg/m <sup>3</sup> Mercury divalent inorganic compounds including mercuric oxide and mercuric chloride (measured as mercury); United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (Mercury, Inorganic forms, as Hg; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
<b>potassium iodide (7681-11-0)</b>		
Belgium	Limit value (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (Iode et iodures (vapeur et aérosol); Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	0.01 ppm (Iode et iodures (vapeur et aérosol); Belgium; Time-weighted average exposure limit 8 h)
USA - ACGIH	ACGIH TWA (ppm)	0.01 ppm (Iodides; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
<b>sodium hydroxide, caustic soda (1310-73-2)</b>		
Belgium	Local name	Sodium (hydroxyde de) # Natriumhydroxide
Belgium	Limit value (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Belgium	Remark (BE)	M: La mention M indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.# De vermelding M duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. het meetresultaat wordt dan gerelateerd aan de beschouwde periode
Croatia	Local name	Natrijev hidroksid; (kaustična soda)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Croatia	Naznake (HR)	C (nagrizajuće)

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



sodium hydroxide, caustic soda (1310-73-2)		
Ireland	Local name	Sodium hydroxide
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Romania	Local name	Hidroxizi alcalini exprimati în hidroxid de sodium
Romania	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Romania	OEL STEL (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Slovenia	Local name	natrijev hidroksid
Slovenia	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Slovenia	KTV factor SL	1
Spain	Local name	Hidróxido de sodio
Spain	VLA-EC (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA - OSHA	Local name	Sodium hydroxide
USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

## 8.2. Exposure controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Hand protection:

Protective gloves

### Eye protection:

Protective goggles

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless. According to product specification.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 0 °C
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 23 hPa (at 20 °C)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.001 g/cm <sup>3</sup> (20 °C)
Solubility	: Miscible with water.
Log Pow	: No data available

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>potassium hydrogen phthalate (877-24-7)</b>	
LD50 oral rat	> 3200 mg/kg (Rat)
<b>mercury diiodide (7774-29-0)</b>	
LD50 oral rat	18 mg/kg (Rat)
<b>potassium iodide (7681-11-0)</b>	
LD50 oral rat	2779 mg/kg (Rat)
LD50 dermal rabbit	3160 mg/kg (Rabbit)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

<b>mercury diiodide (7774-29-0)</b>	
Threshold limit algae 1	0.16 mg/l (LC50; 18 h)
<b>potassium iodide (7681-11-0)</b>	
LC50 fish 1	1788.85 mg/l (LC50; 96 h)
EC50 Daphnia 1	483.68 mg/l (LC50; 48 h)

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



<b>sodium hydroxide, caustic soda (1310-73-2)</b>	
LC50 fish 1	> 35 mg/l
EC50 other aquatic organisms 1	> 33 mg/l waterflea

### 12.2. Persistence and degradability

<b>mercury diiodide (7774-29-0)</b>	
Persistence and degradability	Biodegradability: not applicable. Forming sediments in water. Biodegradability in soil: not applicable. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

<b>potassium iodide (7681-11-0)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

### 12.3. Bioaccumulative potential

<b>potassium hydrogen phthalate (877-24-7)</b>	
Log Pow	-2.73
Bioaccumulative potential	Bioaccumulation: not applicable.

<b>mercury diiodide (7774-29-0)</b>	
Bioaccumulative potential	Bioaccumulative.

<b>potassium iodide (7681-11-0)</b>	
Bioaccumulative potential	Not bioaccumulative.

<b>sodium hydroxide, caustic soda (1310-73-2)</b>	
Log Pow	-3.88

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



ADR	IMDG	IATA	ADN	RID
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association



# BUFFER SOLUTION PH 5.00 ± 0.01

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 31/10/2017 Version: 0.0

Doc. No: SDS-908.B05/1



IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:	
Acute Tox. 1 (Dermal)	Acute toxicity (dermal), Category 1
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS ISOLAB

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*