

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Xylenes

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ISOLAB Laborgeräte GmbH
Am Dillhof 2 - 63863 Eschau / GERMANY
Tel: + 49 93 74 / 978 55-0
Fax: +49 93 74 / 978 55-29
prodsafe@isolab.de

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Giftnotruf der Charité CBF, Haus VIII (Wirtschaftgebäude), UG	Hindenburgdamm 30 12203 Berlin	+49 30 19240	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226
Acute Tox. 4 (Dermal) H312
Eye Irr. 2 H319
Acute Tox. 4 (Inhalation:vapour) H332
Skin Irrit. 2 H315
STOT SE 3 H335
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Xylenes, ethyl benzene

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed..
P241 - Use explosion-proof equipment.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P280 - Wear protective gloves/ protective clothing.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor
P303+361+353 - Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P370+ P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylenes	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	<= 100	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	< 25	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830
Date of issue: 24/11/2017 Version: 0.0
Doc No: SDS-990.019/1



5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. NO open flames, NO sparks, and NO smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
Austria	Local name	Ethylbenzol
Austria	MAK (mg/m ³)	440 mg/m ³
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m ³)	880 mg/m ³
Austria	MAK Short time value (ppm)	200 ppm
Austria	Remark (AT)	H
Belgium	Local name	Ethylbenzène # Ethylbenzeen
Belgium	Limit value (mg/m ³)	442 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m ³)	551 mg/m ³
Belgium	Short time value (ppm)	125 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



ethylbenzene (100-41-4)		
Belgium	Remark (BE)	D: La mention D signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # De vermelding D betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Bulgaria	Local name	Етилбензен
Bulgaria	OEL TWA (mg/m ³)	435 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	545 mg/m ³
Bulgaria	Notes	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Croatia	Local name	Etilbenzen
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	442 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	884 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	200 ppm
Croatia	Naznake (HR)	K (Skin): (naznaka da tvar može štetno djelovati kroz kožu); EU* (naznaka da se radi o tvarima za koje su utvrđene indikativne granične vrijednosti izloženosti prema Direktivi 2000/39/ EC (prva lista)); F (lako zapaljivo); Xn (Štetno)
Czech Republic	Local name	Ethylbenzen
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	500 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	120 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Ethylbenzen
Denmark	Grænseværdie (langvarig) (mg/m ³)	217 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Estonia	Local name	Etüülbenseen
Estonia	OEL TWA (mg/m ³)	442 mg/m ³
Estonia	OEL TWA (ppm)	100 ppm
Estonia	OEL STEL (mg/m ³)	884 mg/m ³
Estonia	OEL STEL (ppm)	200 ppm
Finland	Local name	Etylibentseeni
Finland	HTP-arvo (8h) (mg/m ³)	220 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	880 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	200 ppm
Finland	Huomautus (FI)	iho
France	Local name	Ethylbenzène
France	VME (mg/m ³)	88.4 mg/m ³
France	VME (ppm)	20 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



ethylbenzene (100-41-4)		
France	VLE (mg/m ³)	402 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Germany	Local name	Ethylbenzol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	88 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Germany	Remark (TRGS 900)	DFG,H,Y,EU
Gibraltar	Eight hours mg/m ³	442 mg/m ³
Gibraltar	Eight hours ppm	100 ppm
Gibraltar	Short-term mg/m ³	884 mg/m ³
Gibraltar	Short-term ppm	200 ppm
Gibraltar	Name of agent	Ethylbenzene
Gibraltar	Notation	Skin
Greece	OEL TWA (mg/m ³)	435 mg/m ³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m ³)	545 mg/m ³
Greece	OEL STEL (ppm)	125 ppm
Hungary	Local name	ETILBENZOL
Hungary	AK-érték	442 mg/m ³
Hungary	CK-érték	884 mg/m ³
Hungary	Megjegyzések (HU)	b, i, l.
Ireland	Local name	Ethylbenzene
Ireland	OEL (8 hours ref) (mg/m ³)	442 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m ³)	884 mg/m ³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Etilbenzene
Italy	OEL TWA (mg/m ³)	442 mg/m ³
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m ³)	884 mg/m ³
Italy	OEL STEL (ppm)	200 ppm
Italy	Notes	pelle
Latvia	Local name	Etilbenzols
Latvia	OEL TWA (mg/m ³)	442 mg/m ³
Latvia	OEL TWA (ppm)	100 ppm
Latvia	OEL STEL (mg/m ³)	884 mg/m ³
Latvia	OEL STEL (ppm)	200 ppm
Lithuania	Local name	Etilbenzenas
Lithuania	IPRV (mg/m ³)	442 mg/m ³
Lithuania	IPRV (ppm)	100 ppm
Lithuania	TPRV (mg/m ³)	884 mg/m ³
Lithuania	TPRV (ppm)	200 ppm
Lithuania	Remark (LT)	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Luxembourg	Local name	Ethylbenzène
Luxembourg	OEL TWA (mg/m ³)	442 mg/m ³
Luxembourg	OEL TWA (ppm)	100 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



ethylbenzene (100-41-4)		
Luxembourg	OEL STEL (mg/m ³)	884 mg/m ³
Luxembourg	OEL STEL (ppm)	200 ppm
Malta	Local name	Ethylbenzene
Malta	OEL TWA (mg/m ³)	442 mg/m ³
Malta	OEL TWA (ppm)	100 ppm
Malta	OEL STEL (mg/m ³)	884 mg/m ³
Malta	OEL STEL (ppm)	200 ppm
Netherlands	Local name	Ethylbenzeen
Netherlands	Grenswaarde TGG 8H (mg/m ³)	215 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	430 mg/m ³
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Poland	Local name	Etylobenzen
Poland	NDS (mg/m ³)	200 mg/m ³
Poland	NDSch (mg/m ³)	400 mg/m ³
Portugal	Local name	Etilbenzeno
Portugal	OEL TWA (ppm)	20 ppm
Romania	Local name	Etilbenzen
Romania	OEL TWA (mg/m ³)	442 mg/m ³
Romania	OEL TWA (ppm)	100 ppm
Romania	OEL STEL (mg/m ³)	884 mg/m ³
Romania	OEL STEL (ppm)	200 ppm
Slovakia	Local name	Etylbenzén
Slovakia	NPHV (priemerná) (mg/m ³)	442 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	OEL STEL (mg/m ³)	884 mg/m ³
Slovakia	OEL STEL (ppm)	200 ppm
Slovakia	Upozornenie (SK)	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Slovenia	Local name	etilbenzen
Slovenia	OEL TWA (mg/m ³)	442 mg/m ³
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m ³)	884 mg/m ³
Slovenia	OEL STEL (ppm)	200 ppm
Slovenia	KTV factor SL	2
Spain	Local name	Etilbenceno
Spain	VLA-ED (mg/m ³)	441 mg/m ³
Spain	VLA-ED (ppm)	100 ppm
Spain	VLA-EC (mg/m ³)	884 mg/m ³
Spain	VLA-EC (ppm)	200 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



ethylbenzene (100-41-4)		
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento) , VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
Sweden	Local name	Etylbensen
Sweden	nivågränsvärde (NVG) (mg/m ³)	220 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	884 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	200 ppm
Sweden	Anmärkning (SE)	H (Ämnet kan lätt upptas genom huden Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
United Kingdom	Local name	Ethylbenzene
United Kingdom	WEL TWA (mg/m ³)	441 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	552 mg/m ³
United Kingdom	WEL STEL (ppm)	125 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Iceland	Local name	Etylbensen
Iceland	OEL (8 hours ref) (mg/m ³)	200 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	50 ppm
Iceland	OEL (15 min ref) (mg/m ³)	884 mg/m ³
Iceland	OEL (15 min ref) (ppm)	200 ppm
Iceland	Notes (IS)	H
Russian Federation	Local name	Этилбензол
Russian Federation	OEL Ceiling (mg/m ³)	150 mg/m ³
Russian Federation	OEL TWA (mg/m ³)	50 mg/m ³
Russian Federation	Remark (RU)	4 класс опасности - умеренно опасное; п (пары и/или газы)
Norway	Local name	Etylbenzen
Norway	Grenseverdier (AN) (mg/m ³)	20 mg/m ³
Norway	Grenseverdier (AN) (ppm)	5 ppm
Norway	Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); K (Kjemikalier som skal betraktes som kreftfremkallende); E (EU har en veiledende grenseverdi for stoffet)
Switzerland	Local name	Ethylbenzol
Switzerland	MAK (mg/m ³)	220 mg/m ³
Switzerland	MAK (ppm)	50 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



ethylbenzene (100-41-4)		
Switzerland	KZGW (mg/m ³)	220 mg/m ³
Switzerland	KZGW (ppm)	50 ppm
Switzerland	Remark (CH)	H O ¹ B - Niere, Leber ^{KT AN} - NIOSH
Turkey	Local name	Etilbenzen
Turkey	OEL TWA (mg/m ³)	442 mg/m ³
Turkey	OEL TWA (ppm)	100 ppm
Turkey	OEL STEL (mg/m ³)	884 mg/m ³
Turkey	OEL STEL (ppm)	200 ppm
Turkey	Comments	Deri
Australia	Local name	Ethyl benzene
Australia	TWA (mg/m ³)	434 mg/m ³
Australia	TWA (ppm)	100 ppm
Australia	STEL (mg/m ³)	543 mg/m ³
Australia	STEL (ppm)	125 ppm
USA - ACGIH	Local name	Ethyl benzene
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
USA - OSHA	Local name	Ethyl benzene
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Xylenes (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Austria	Local name	Xylol (alle Isomeren)
Austria	MAK (mg/m ³)	221 mg/m ³
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m ³)	442 mg/m ³
Austria	MAK Short time value (ppm)	100 ppm
Austria	Remark (AT)	H
Belgium	Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	442 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D: La mention D signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # De vermelding D betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Bulgaria	Local name	Ксилен (смес от изомери), чист
Bulgaria	OEL TWA (mg/m ³)	221 mg/m ³
Bulgaria	OEL TWA (ppm)	50 ppm
Bulgaria	OEL STEL (mg/m ³)	442 mg/m ³
Bulgaria	OEL STEL (ppm)	100 ppm
Bulgaria	Notes	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



Xylenes (1330-20-7)		
Croatia	Local name	Ksilen (svi izomeri)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	221 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	442 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	Naznake (HR)	K (Skin): (naznaka da tvar može štetno djelovati kroz kožu); EU* (naznaka da se radi o tvarima za koje su utvrđene indikativne granične vrijednosti izloženosti prema Direktivi 2000/39/ EC (prva lista)); Xn (Štetno)
Czech Republic	Local name	Xylen technická sm s isomer a (všechny isomery)
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	50 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	400 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	90 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Xylen (Dimethylbenzen), alle isomere
Denmark	Grænseværdie (langvarig) (mg/m ³)	109 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Estonia	Local name	Ksüleeni (dimetüülbenseen)
Estonia	OEL TWA (mg/m ³)	200 mg/m ³
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m ³)	450 mg/m ³
Estonia	OEL STEL (ppm)	100 ppm
Finland	Local name	Ksyleeni
Finland	HTP-arvo (8h) (mg/m ³)	220 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	Huomautus (FI)	iho
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m ³)	221 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Germany	Local name	Xylol (alle Isomeren)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	440 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm
Germany	Remark (TRGS 900)	DFG,EU,H
Gibraltar	Eight hours mg/m ³	221 mg/m ³
Gibraltar	Eight hours ppm	50 ppm
Gibraltar	Short-term mg/m ³	442 mg/m ³
Gibraltar	Short-term ppm	100 ppm
Gibraltar	Name of agent	Xylene, mixed isomers, pure
Gibraltar	Notation	Skin
Greece	OEL TWA (mg/m ³)	435 mg/m ³
Greece	OEL TWA (ppm)	100 ppm

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



Xylenes (1330-20-7)		
Greece	OEL STEL (mg/m ³)	650 mg/m ³
Greece	OEL STEL (ppm)	150 ppm
Hungary	Local name	XILOL(ok)
Hungary	AK-érték	221 mg/m ³
Hungary	CK-érték	442 mg/m ³
Hungary	Megjegyzések (HU)	b; EU1
Ireland	Local name	Xylene, mixed isomers
Ireland	OEL (8 hours ref) (mg/m ³)	221 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	442 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Xilene, isomeri misti, puro
Italy	OEL TWA (mg/m ³)	221 mg/m ³
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m ³)	442 mg/m ³
Italy	OEL STEL (ppm)	100 ppm
Italy	Notes	pelle
Latvia	Local name	Ksilols (o-,m-,p-ksilols, dimetilbenzols)
Latvia	OEL TWA (mg/m ³)	221 mg/m ³
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL STEL (mg/m ³)	442 mg/m ³
Latvia	OEL STEL (ppm)	100 ppm
Lithuania	Local name	Ksilenas
Lithuania	IPRV (mg/m ³)	200 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	450 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Lithuania	Remark (LT)	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Luxembourg	Local name	Xylène, isomères mixtes, purs
Luxembourg	OEL TWA (mg/m ³)	221 mg/m ³
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m ³)	442 mg/m ³
Luxembourg	OEL STEL (ppm)	100 ppm
Malta	Local name	Xylene, mixed isomers, pure
Malta	OEL TWA (mg/m ³)	221 mg/m ³
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m ³)	442 mg/m ³
Malta	OEL STEL (ppm)	100 ppm
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m ³)	210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	442 mg/m ³

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



Xylenes (1330-20-7)		
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een Haanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Poland	Local name	Ksylan mieszanina izomerów: 1,2-; 1,3-; 1,4-
Poland	NDS (mg/m ³)	100 mg/m ³
Portugal	Local name	Xileno (isómeros)
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	150 ppm
Romania	Local name	Xilen (izomeri)
Romania	OEL TWA (mg/m ³)	221 mg/m ³
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m ³)	442 mg/m ³
Romania	OEL STEL (ppm)	100 ppm
Slovakia	Local name	Xylén, zmiešané izoméry
Slovakia	NPHV (priemerná) (mg/m ³)	221 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	OEL STEL (mg/m ³)	442 mg/m ³
Slovakia	OEL STEL (ppm)	100 ppm
Slovakia	Upozornenie (SK)	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Slovenia	Local name	ksilen (mešane izomere)
Slovenia	OEL TWA (mg/m ³)	221 mg/m ³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m ³)	442 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Slovenia	KTV factor SL	2
Spain	Local name	Xilenos, mezcla isómeros
Spain	VLA-ED (mg/m ³)	221 mg/m ³
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m ³)	442 mg/m ³
Spain	VLA-EC (ppm)	100 ppm
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).
Sweden	Local name	Xylen
Sweden	nivågränsvärde (NVG) (mg/m ³)	221 mg/m ³

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830
Date of issue: 24/11/2017 Version: 0.0
Doc No: SDS-990.019/1



Xylenes (1330-20-7)		
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	442 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	Anmärkning (SE)	H (Ämnet kan lätt upptas genom huden Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
United Kingdom	Local name	Xylene
United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³ o-,m-,p- or mixed isomers
United Kingdom	WEL TWA (ppm)	50 ppm o-,m-,p- or mixed isomers
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³ o-,m-,p- or mixed isomers
United Kingdom	WEL STEL (ppm)	100 ppm o-,m-,p- or mixed isomers
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)
Russian Federation	Local name	Диметилбензол
Russian Federation	OEL Ceiling (mg/m ³)	150 mg/m ³ (смесь 2,3-, 4-изомеров)
Russian Federation	OEL TWA (mg/m ³)	50 mg/m ³ (смесь 2,3-, 4-изомеров)
Russian Federation	Remark (RU)	3 класс опасности - опасное; п (пары и/или газы)
Norway	Local name	Xylen (alle isomere)
Norway	Grønseverdier (AN) (mg/m ³)	108 mg/m ³
Norway	Grønseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); E (EU har en veiledende grønseverdi for stoffet)
Switzerland	Local name	Xylol (alle Isomeren)
Switzerland	MAK (mg/m ³)	435 mg/m ³
Switzerland	MAK (ppm)	100 ppm
Switzerland	KZGW (mg/m ³)	870 mg/m ³
Switzerland	KZGW (ppm)	200 ppm
Switzerland	Remark (CH)	H B - OAW & Auge, ZNS, Schwinde ^{KT HU} - INRS, NIOSH, die MAK für Benzol muss eingehalten werden
Turkey	Local name	Ksilen
Turkey	OEL TWA (mg/m ³)	221 mg/m ³ (karışım izomerleri, saf)
Turkey	OEL TWA (ppm)	50 ppm (karışım izomerleri, saf)
Turkey	OEL STEL (mg/m ³)	442 mg/m ³ (karışım izomerleri, saf)
Turkey	OEL STEL (ppm)	100 ppm (karışım izomerleri, saf)
Turkey	Comments	Deri
USA - ACGIH	Local name	Xylene
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
USA - OSHA	Local name	Xylenes (o-, m-, p-isomers)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 106.17 g/mol
Colour	: Colourless.
Odour	: aromatic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: > -48 °C
Freezing point	: No data available
Boiling point	: 136 - 145 °C at 1,013 hPa
Flash point	: 73 - 81 °F (23 - 27 °C)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 45 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.87 g/cm ³ (20 °C)
Solubility	: Water: 0.2 g/l
Log Pow	: No data available
Viscosity, kinematic	: 0.75 mm ² /s at 25 °C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit	: 1 vol %
Upper explosive limit	: 8 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830
Date of issue: 24/11/2017 Version: 0.0
Doc No: SDS-990.019/1



10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin.

LD50 oral Rat	3523 mg/kg
---------------	------------

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1307	1307	1307	1307	1307
14.2. UN proper shipping name				
XYLENES	XYLENES	Xylenes	XYLENES	XYLENES
Transport document description				
UN 1307 XYLENES, 3, III, (D/E)	UN 1307 XYLENES, 3, III (23°C c.c.)	UN 1307 Xylenes, 3, III	UN 1307 XYLENES, 3, III	UN 1307 XYLENES, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1




ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

- Transport by sea

Special provisions (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Flash point (IMDG)	: 23°C to 30°C c.c.
Properties and observations (IMDG)	: Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7% Immiscible with water.

- Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

- Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to waters (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



NIET-limitatieve lijst van voor de voortplanting : xylene is listed
giftige stoffen – Ontwikkeling

Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H304;H312+H332;H315;H373>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

SDS	Safety Data Sheet
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Eye Irr. 2	Serious eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure.

Xylenes

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 24/11/2017 Version: 0.0

Doc No: SDS-990.019/1



SDS ISOLAB

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product